

HOSE CONNECTION VACUUM BREAKERS



The Hose Connection Vacuum Breaker is designed to prevent back siphonage through a hose connected to a safe drinking water supply.

Catalogue Numbers

Model	Catalogue Numbers
20mm	7105
20mm chrome	7105.2
25mm	7107
25mm chrome	7107.2

It comprises a single check valve, spring loaded to the closed position with an atmospheric vacuum breaker vent.

Application

The Hose Connection Vacuum Breakers provide protection to the potable water supply from contamination in low hazard applications such as flexible connections over domestic fixtures and external hose taps.

Inlet:	Female BSP
Outlet:	Male BSP
Maximum working pressure:	1400 kPa
Maximum temperature:	80°C

Materials


Body:	Brass or chrome plated brass
Spring:	Stainless steel



Features and Benefits

- Corrosion resistant
- Choice of brass or chrome plated finish
- Brass body
- Suitable for hot or cold water service (up to 80°C at 1400 kPa)
- Durable
- Maximum working pressure of 1400 kPa
- “Breakaway” set screw protects against tampering
- Approved to AS2845.1

Dimensions



7105 / 7107	20mm	25mm
A. Length	28mm	28mm
B. Diameter	36mm	38mm

* Dimensions may be changed without notice



Uniquely Australian