

# WATER SERVICE BALL VALVE



The Reliance Isolating Ball Valves are a proven industry leading design and Watermarked to both AS4796 and AS5200.



| Model                                 | Catalogue Number |
|---------------------------------------|------------------|
| <b>Water Service Ball Valves</b>      |                  |
| Long Handle 20 F x 20 F               | BVLH75FF         |
| Long Handle 20 M x 20 F               | BVLH75MF         |
| Long Handle Recycled 20 M x 20 F      | BVLH75MF-R       |
| Long Handle 25 M x 25 F               | BVLH25MF         |
| Long Handle Recycled 25 M x 25 F      | BVLH25MF-R       |
| Short Handle Straight Ball Valve DN20 | BVSH75MF         |
| <b>Water Service Ball Valves 90°</b>  |                  |
| 20 F x 20 F                           | RB9020FF         |
| 20 F x 20 F Stainless Steel *         | RB9020FF-SS      |
| 20 F x 20 M                           | RB9020FM         |
| 20 C x 20 F                           | RB9020CF         |
| 20 F X 20 F Recycled                  | RB9020FF-R       |
| 20 C x NSW Meter Coupling             | RB900            |
| 20 F x NSW Meter Coupling             | RB902            |
| 25 F x 25 F                           | RB9025FF         |
| 20 C x 20 BSP Meter Coupling Recycled | RB904-R          |
| 25 F x 25 NSW Meter Coupling          | JB250            |
| 25 F x 25 Meter Coupling              | JB251            |
| * Full Stainless Steel Construct      |                  |

- ### Features and Benefits
- Forged DR Gunmetal Body
  - Bottom loading, dual o-ring sealed stem
  - Resilient seats
  - Right Angle (F-F) and Straight Through (M-F, F-F) versions
  - Lockable in either Open or Closed position
  - Max pressure: 1600 kPa
  - Max Temperature: 60°C
  - Common base connection configuration
  - Long life performance through its high quality components
  - Light weight construction for ease of handling
  - Quality guaranteed Water Marked product
  - Lilac handled ball valves for recycled applications

### Description

The Water Service Ball Valve range comes in sizes from 20mm to 25mm, in both right angle and straight configurations. Reliance can also supply a range of fittings (compression, capillary etc.) to suit most connection needs.

Note: Product material configuration may vary over size range.

