

WATER SERVICE BALL VALVE



The Reliance Isolating Ball Valves are a proven industry leading design and Watermarked to both AS4796 and AS5200.



Model	Catalogue Number
-------	------------------

Water Service Ball Valves

Long Handle 20 F x 20 F	BVLH75FF
Long Handle 20 M x 20 F	BVLH75MF
Long Handle Recycled 20 M x 20 F	BVLH75MF-R
Long Handle 25 M x 25 F	BVLH25MF
Long Handle Recycled 25 M x 25 F	BVLH25MF-R
Lockable 25 F x 25 F	J1900WBS
Short Handle Straight Ball Valve DN20	BVSH75MF

Water Service Ball Valves 90°

20 F x 20 F	RB9020FF
20 F x 20 F Stainless Steel *	RB9020FF-SS
20 F x 20 M	RB9020FM
20 C x 20 F	RB9020CF
20 F X 20 F Recycled	RB9020FF-R
20 C x NSW Meter Coupling	RB900
20 F x NSW Meter Coupling	RB902
25 F x 25 F	RB9025FF
20 C x 20 BSP Meter Coupling Recycled	RB904-R
25 F x 25 NSW Meter Coupling	JB250
25 F x 25 Meter Coupling	JB251

* Full Stainless Steel Construct

Description

The Water Service Ball Valve range comes in sizes from 20mm to 25mm, in both right angle and straight configurations. Reliance can also supply a range of fittings (compression, capillary etc.) to suit most connection needs.

Note: Product material configuration may vary over size range.

Features and Benefits

- Forged DR Gunmetal Body
- Bottom loading, dual o-ring sealed stem
- Resilient seats
- Right Angle (F-F) and Straight Through (M-F, F-F) versions
- Lockable in either Open or Closed position
- Max pressure: 1600 kPa
- Max Temperature: 60°C
- Common base connection configuration
- Long life performance through its high quality components
- Light weight construction for ease of handling
- Quality guaranteed Water Marked product
- Lilac handled ball valves for recycled applications



Uniquely Australian