

Y-STRAINERS

RMC's Y-Strainers provide downstream protection from dirt and debris. Available with female threaded connections.

Model	Size	Catalogue Number
DN15	15mm	7191
DN20	20mm	7192
DN25	25mm	7193
DN32	32mm	7194
DN40	40mm	7195
DN50	50mm	7196

Application

The RMC Y-Strainers can be installed upstream of any valve that requires protection from dirt and debris. The Y-Strainer should be installed with the arrow marking on the body in line with the system's flow direction. Easy access to the strainer cap is required for removal and cleaning.

Technical Specifications

Temperature range 0°C - 99°C

Max. working pressure 2000 kPa

Mesh size 500 microns

Materials

Body DZR Brass

Cap DZR Brass

Strainer Stainless Steel

Seals EPDM



Features and Benefits

- Robust DZR brass body
- Easily removable cap for strainer access and cleaning
- 500 micron mesh to catch debris and impurities in the water
- Meets Australian Standard for potable water supply
- Every valve is tested to ensure high quality and performance

Dimensions

Model	A	B	C
7191	G 1/2" Female	39	67
7192	G 3/4" Female	50	81
7193	G 1" Female	55	97
7194	G 1 1/4" Female	66	104
7195	G 1 1/2" Female	75	118
7196	G 2" Female	90	145

