

# Y-Strainer

## Scope of Use / Specification Sheet

RMC's Y-Strainers provide downstream protection from dirt and debris. Available with female threaded connections.



7196

### Product Code

Model	Size	Product Code
DN15	15mm	7191
DN20	20mm	7192
DN25	25mm	7193
DN32	32mm	7194
DN40	40mm	7195
DN50	50mm	7196

### Application

The RMC Y-Strainers can be installed upstream of any valve that requires protection from dirt and debris. The Y-Strainer should be installed with the arrow marking on the body in line with the system's flow direction. Easy access to the strainer cap is required for removal and cleaning.

### Installation Conditions

Working Temperature Range	0°C to 99°C
Maximum Working Pressure	2000kPa
Mesh Size	500 microns

### Features and Benefits

- Robust DZR brass body
- Easily removable cap for strainer access and cleaning
- 500 micron mesh to catch debris and impurities in the water
- Meets Australian Standard for potable water supply
- Every valve is tested to ensure high quality and performance

### Warranty

Reliance Worldwide Corporation (Aust.) Pty. Ltd. (RWC) will either replace or repair any defective goods where the defect arose as a result of manufacture within the warranty period. You may contact RWC at the phone number, address or e-mail shown below for further information or to make a claim.

Visit [www.rmc.com.au/warranty](http://www.rmc.com.au/warranty) to view the warranty statement in full and for further important information.

### Installation

Installation is subject to the requirements of the applicable regulatory authority, the National Construction Code Volume Three – Plumbing Code of Australia, associated reference standards as applicable at the time and AS/NZS 3500.1.

### Standards and Approvals



AS 3688  
WM-022217

# Y-Strainer

Dimensions			
Model	A	B	C
7191	G 1/2" Female	39	67
7192	G 3/4" Female	50	81
7193	G 1" Female	55	97
7194	G 1 1/4" Female	66	104
7195	G 1 1/2" Female	75	118
7196	G 2" Female	90	145

Materials	
Body	DZR Brass
Cap	DZR Brass
Strainer	Stainless Steel
Seals	EPDM

Note: All measurements in mm unless otherwise stated.

