WHY RWC WATER METERS?

Reliance Worldwide Corporation (RWC) supplies a range of water meters suitable for hot and cold water, domestic, commercial and industrial applications.

Our meters conform to Australian standards and are available in configurations suitable for each state in Australia.

We also supply water valves that conform to selected international standards. A range of automatic reading products and logging/monitoring products are available to compliment our water meter products.





YOUR GUIDE TO WATER METERS



Contents of this brochure are subject to change, please visit our website for most up-to-date product information.





Commercial







1800 810 803



sales.au@rwc.com



rmc.com.au

27-28 Chapman Place, Eagle Farm QLD 4009, Australia



Reliance Worldwide Corporation (Aust.) Pty. Ltd. ABN 71 004 784 301 | AU-RMC-MN0165R2

RWC WATER METERING PRODUCT RANGE

- Positive Displacement Meters
- Multijet Water Meters
- Octave Ultrasonic Meters
- Woltman Meters
- Hot Water Meters
- Sub Metering Kits
- Tapping Kits
- Ball Valves
- Tapping Bands
- Ferrule Cocks & Bends
- Meter Boxes
- Standpipes
- Reed Switches & Pulse Outputs

Positive Displacement Meter

 Size
 15-20mm

 Pulse
 1P / 5l

 Max. Water Temp.
 50°C

 Max. Working Pressure
 1600kPa

 NMI Approved

NMI Approve WaterMark

WaterMark Approved



Sub Metering Kits

- 20mm
- Available in different configurations; Meter Thread - STD copper connection NSW Thread - STD copper connection
- Also available in SharkBite® copper and PEX connections



Multiiet Meter

Approval

Approval

 Size
 20-40mm

 Pulse
 1P/10l

 Max. Water Temp.
 50°C

 Max. Working Pressure
 1400kPa

NMI Approved WaterMark Approved

(20mm, 25mm only)



Tapping Kits

- Rapid tap for 20-25mm tapping
- For pressure and dry taps
- Major tap for 32-50mm
- · Watgas for 150mm tapping



Octave Ultrasonic Meter

 Size
 50-300mm

 Pulse
 1P/10L/100L/100L/1000L

 Max. Water Temp.
 50°C

 Max. Working Pressure
 1600kPa

 Approval
 NMI Approved



Ball Valves

- Watermarked
- · Long, straight or short handle
- Lockable, right angle configuration
- Stainless Steel option available



Woltman Meter

 Size
 50-200mm

 Pulse
 1P / 101 / 1001 / 10001

 Max. Water Temp.
 60°C

 Max. Working Pressure
 1600kPa

 Approval
 NMI Approved



Tapping Bands

- WaterMark Approved (select types and sizes)
- · AC/DI & PVC Pipe
- · 3/4 2" BSP outlet







Polymer Positive Displacement Meter

WM151PD	15mm BSP Thd
WM211PD	20mm NSW Thd
WM212PD	20mm Meter Thd
WM213PD	20mm BSP Thd



Endurance Multijet

WM273MRP	20mm Mete	er Thd
WM274MRP	20mm NSW	/ Thd
WM275MRP	20mm BSP	Thd
WM281MRP	20mm BSP	Thd – Lavender
WM270MRP	25mm NSW	Thd
WM271MRP	25mm Mete	r Thd
WM272MRP	25mm BSP	Thd
WM322MRP*+	32mm Oval	Flange (Single Check)
WM402MRP*+	40mm Oval Flange	
WM514MRP+	50mm	300mm (L)

Installation: Horizontal only

* Non-Trade use only + APPROVED UTILITY USE ONLY. NO WATERMARK.



WM5000CT - POLY	50mm Ultrasonic
WM500OCTSST	50mm Ultrasonic
WM500OCTSS+	50mm Ultrasonic
WM800OCTSS+	80mm Ultrasonic
WM1000OCTSS+	100mm Ultrasonic
WM1500OCTSS+	150mm Ultrasonic
WM2000OCTSSHF+	200mm Ultrasonic

+ APPROVED UTILITY USE ONLY. NO WATERMARK.



Woltman – Industrial ISO Length

WM:	500WST	50mm Woltman	200mm (L)
WM	650WST	65mm Woltman	200mm (L)
WM	800WST	80mm Woltman	230mm (L)
WM	1000WST	100mm Woltman	250mm (L)
WM	1500WST	150mm Woltman	300mm (L)

APPROVED UTILITY USE ONLY. NO WATERMARK. Flanged Table D



Woltman - Industrial Australian Length

WM501WST	50mm Woltman	311mm (L)
WM801WST	80mm Woltman	413mm (L)
WM1001WST	100mm Woltman	483mm (L)
WM1501WST	150mm Woltman	500mm (L)
WM2001WST	200mm Woltman	520mm (L)

APPROVED UTILITY USE ONLY. NO WATERMARK.

WATER METERS KITS



Recycled Water Kits

7255	M 5/8"	
7260	M 5/8"	
7265	F 5/8" (15mm x 150mm)	
7270	F 5/8" (15mm x 300mm)	
7275	F 5/8" (20mm x 150mm)	
7280	F 5/8" (20mm x 300mm)	
7281	Recycled Water Hose Bib Kit	
12615	Lilac Key for Tan	



Sub Metering Kits

KIT227EX	Bracket With Extendible Coupling
KIT227Q	Bracket QUU
KIT228	Kit – PEX
KIT229	Kit – SharkBite
KIT232	Kit – DN20 NSW
KIT233	Kit – DN20 NSW + Spacer



Water Meter Boxes			
WM90	368L x 271W x 316D – c/w Black Lid		
WMBOX200	492L x 271W x 220D - c/w Black Lid		
	Large Shallow (Taper)		
WMBOX202	430L x 270W x 220D – Low Profile		
WMBOX203	430L x 270W x 275D – High Profile		
WMBOX204	Lge, Rev Taper – c/w Green Lid, No Base		
WMBOX206	Dradual 600/1		
WMBOX209	Base to suit WMBOX204		
KIT237	Assembled with MI Ends – 20mm BSP		
KIT238	Assembled with PE Ends		
WMLID	Lid – Galvanised Steel		



Water Meter Kits

WMKIT211	20mm Thd c/w Couplings (MC208)
WMKIT211WA	20mm Thd c/w Couplings (MC202)
WMKIT211R	20mm Thd Recycled
WMKIT271	25mm Thd c/w Couplings (1N131)
WMKIT230	20mm PD Thd – c/w Couplings
WMKIT231	20mm PD NSW Thd - c/w Couplings
WMKIT272	25mm PD Thd – c/w Couplings
WMKIT273	25mm PD NSW Thd – c/w Couplings

METER DIRT BOXES



Meter Dirt Boxes

1N114	Flanged 50mm	200mm (L)
1N111	Flanged 80mm	225mm (L)
1N112	Flanged 100mm	250mm (L)
1N113	Flanged 150mm	300mm (L)

BALL VALVES & COUPLINGS



Water Service Ball Valves

BVLH75FF*	Long Handle 20mm F x 20mm F
BVLH75MF*	Long Handle 20mm M x 20mm F
BVLH25MF*	Long Handle 25mm M x 25mm F
BVSH75MF	Short Handle Straight DN20
	(Not Lockable)



Water Service Ball Valves – Recycle Water Service Ball Valves

	-	
BVLH75MF-R	Long Handle 20mm	
BVLH25MF-R	Long Handle 25mm	
RB9020FF-R	90° 20mm F x 20mm F	



RB9020FF	20mm F x 20mm F
RB9020FM	20mm F x 20mm M
RB9020CF	20mm C x 20mm F
RB9020FF-SS	20mm F x 20mm F
RB900*	20mm C x NSW
RB902*	20mm F x NSW
RB9025FF	25mm F x 25mm F
JB250*	25mm F x 25mm NSW
JB251*	25mm F x 25mm

Lockable in either open or closed position

* Meter Coupling



Meter Flange, Seal and Bolt Kits

1N148*	Oval Flange Kit 32mm
1N149*	Oval Flange Kit 40mm
1N154**	Round Flange Kit 50mm
1N155**	Round Flange Kit 80mm
* Oval Flang	e Kits contain 1 Flange, 1 Seal, and 2 Bolt.
**Round Flar	nge Kits contain 1 Flange, 1 Seal, and Bolts

(to suit Table D)





Meter	Couplings		
MC150	BSP 15mm M	MC250	BSP 25mm M
MC207	NSW 20mm F	MC215	NSW 20mm FE
MC206	NSW 20mm F	MC216**	20mm F Ext
	Short	1N131**	25mm M
MC201	NSW 20mm M	1N141	NSW 25mm M
MC208**	20mm M	1N142	NSW 25mm F
MC204**	BSP 20mm M	MC400	BSP 40mm M

WATER MAINS ACCESSORIES



SURESEAL Tapping Bands Series 1 SURESEAL Tapping Bands Series 2 White PVC Pipe

	-		
12012*	50mm x 25mm	12063*	150mm x 32mm
12014*	63mm x 20mm	12064*	150mm x 40mm
	Poly	12065*	150mm x 50mm
12015*	63mm x 25mm	12086	200mm x 20mm
	Poly	12087	200mm x 25mm
12031*	80mm x 20mm	12089	200mm x 40mm
12032*	80mm x 25mm	12090*	*200mm x 50mm
12034*	80mm x 40mm	12091	225mm x 20mm
12035*	80mm x 50mm	12092	225mm x 25mm
12041*	100mm x 20mm	12101	250mm x 20mm
12042*	100mm x 25mm	12102	250mm x 25mm
12043*	100mm x 32mm	12105**	250mm x 50mm
12044*	100mm x 40mm	12121	300mm x 20mm
12045*	100mm x 50mm	12122	300mm x 25mm
12061*	150mm x 20mm	12125**	300mm x 50mm
12062*	150mm x 25mm		

White PVC Pipe Series 1 – Full Circle Model.

* Standard with s/s bolts. Insulation may be required for Bi-Metallic contact.

** Use reducing bushes to accommodate any smaller offtake.



Ac & Compatible Pipe

mm x 25mm	12063*	150mm x 32mm	12137*	58mm x 20mm	12185*	200mm x 50n
nm x 20mm	12064*	150mm x 40mm	12138*	58mm x 25mm	12191	225mm x 20m
У	12065*	150mm x 50mm	12141*	80mm x 20mm	12192	225mm x 25m
nm x 25mm	12086	200mm x 20mm	12142*	80mm x 25mm	12195	225mm x 50m
У	12087	200mm x 25mm	12145*	80mm x 50mm	12201	250mm x 20m
mm x 20mm	12089	200mm x 40mm	12151*	100mm x 20mm	12202	250mm x 25m
mm x 25mm	12090*	*200mm x 50mm	12152*	100mm x 25mm	12205	250mm x 50m
mm x 40mm	12091	225mm x 20mm	12153*	100mm x 32mm	12221	300CD x 20m
mm x 50mm	12092	225mm x 25mm	12154*	100mm x 40mm	12222	300CD x 25mi
mm x 20mm	12101	250mm x 20mm	12155*	100mm x 50mm	12225	300CD x 50m
mm x 25mm	12102	250mm x 25mm	12171*	150mm x 20mm	12231+	375mm x 20m
mm x 32mm	12105**	250mm x 50mm	12172*	150mm x 25mm	12232+	375mm x 25m
mm x 40mm	12121	300mm x 20mm	12173*	150mm x 32mm	12235+	375mm x 50m
mm x 50mm	12122	300mm x 25mm	12174*	150mm x 40mm	12245+	450mm x 50n
mm x 20mm	12125**	300mm x 50mm	12175*	150mm x 50mm	12255+	500mm x 50r
mm x 25mm			12181*	200mm x 20mm	12275+	600mm x 50r
e Series 1 – Full Circ	cle Model.		12182*	200mm x 25mm		

Standard with s/s bolts. Insulation may be required for Bi-Metallic contact.

APPROVED UTILITY USE ONLY, NO WATERMARK.



Ferrule Cocks

x 50mm	113
x 20mm	113
x 25mm	113
x 50mm	113
x 20mm	113
x 25mm	110
x 50mm	110
20mm	110
25mm	110
50mm	110
x 20mm	110
x 25mm	Out
x 50mm	
x 50mm	
x 50mm	



301	20mm Standard	11012	25mm Bonnet
302	25mm Standard	11013	32mm Bonnet
303	32mm Standard	11014	40mm Bonnet
304	40mm Standard	11015	50mm Bonnet
305	50mm Standard	11021	20mm x 25mm
001	20mm Capped		Capped Poly
002	25mm Capped	11022	25mm x 32mm Capped Poly
003	32mm Capped	11001	
004	40mm Capped	11081	20mm x 25mm Bonnet Poly
005	50mm Capped	11082	25mm x 32mm
O11	20mm Bonnet	11002	Bonnet Poly

utlet connection to suit Ferrule Bends only



Ferrule Bends

17002	20mm Capillary Copper
17003	25mm Capillary Copper
11041	20mm Compression
1042	25mm Compression
1043	32mm Compression
1044	40mm Compression
1045	50mm Compression
11051	20mm Male BSP
1052	25mm Male BSP
1053	32mm Male BSP
11054	40mm Male BSP
1055	50mm Male BSP
1062	25mm Male RSD



WA 20mm M



Standpipes – Metered

WM264MSP	25mm BSP Thread
WM257MSPTAP	25mm Stand Pipe w/ 20mm Tap
WM326MSP	32mm BSP Thread (high flow)
WM654MSP	65mm BSP Thread
WM656MSPCFA	65mm CFA Thread
WM657MSPQLD	65mm QLD Round Thread
WM658MSPNSW	65mm NSW Thread

Servicing available



SURESEAL Tapping Bands Maintenance Type

12342	80mm x 25mm	12375*	150mm x 50mm
12351	100mm x 20mm	12392	225mm x 25mm
12352	100mm x 25mm	12395*	225mm x 50mm
12355	100mm x 50mm	12397	300mm x 25mm
12371	150mm x 20mm	12400*	300mm x 50mm
12372	150mm x 25mm		

APPROVED UTILITY USE ONLY. NO WATERMARK.

"Use reducing bushes to accommodate smaller off takes. Tapping Saddle Maintenance Type for use on AC or oversize AC pipe. Designed with 50mm wide flexible band to better accommodate pipe size and shape variations.



SURESEAL Coated Tapping Bands Ferrule Bonnet Assemblies

	0 <u>=</u> , (= 000,100	. ~ [
12501	100mm x 20mm	
12502	100mm x 25mm	
12506	150mm x 20mm	
12507	150mm x 25mm	
Standard w	ith s/s holts. Insulation may	v he re



	201111017 1000111101100
11691	20mm Ferrule Bonnet Assembly
11692	25mm Ferrule Bonnet Assembly
11693	32mm Ferrule Bonnet Assembly
11694	40mm Ferrule Bonnet Assembly
11695	50mm Ferrule Bonnet Assembly



Tapping Kits

10010	Rapid Tap Main Tapping Kit 20-25mm
10500	Major Tapping Kit 40-50mm
10700	WATGAS Boring Machine
Servicing an	rd spare parts available



Standpipes – Non-Metered

	•
FS3021	65mm CFA
FS3027	65mm FBT
FS3036	65mm QRT
FS3040	65mm Storz

Servicing available

REED SWITCH & PULSE OUTPUTS



Remote Digital Display

WMPC2 Flexi-Reader Pulse Counter
WMPC4 Battery Holder



Cold Water Meters

WM598 20-40mm Multijet - 1 pulse / 10l WMRS5-5 15-25mm PD Meter - 1 pulse / 5l





Octave Meter Accessories


WMR010	4-20 mA Output
WMR011	Dual Pulse Output
WMR012	SSR Output
WMR013	M-Bus Output
WMR014	MODBUS Output



Cold Water Woltman Meter

Cold Water	Wottimaniwictor	
WMSP011*	50mm – 1 pulse / 10l	
WMSP014*	65mm – 1 pulse / 10l	
WMSP012*	80mm - 1 pulse / 10l	
WMSP013*	100mm – 1 pulse / 10l	
WMSP004*	150mm – 1 pulse / 1000l	
WMSP005*	200mm – 1 pulse / 1000l	
WMRS6	Cable only	





* Register included