


Gas Flexible Hose Connectors

Scope of Use / Specification Sheet

The RMC range of Gas Flexible Hoses in Class D & Class B are available in lengths from 300mm – 1200mm.



Product Code

Size	Connection	Length	Product Code
10mm	15FC x 15MI	450mm	FCG001
		600mm	FCG002
		900mm	FCG003
		1000mm	FCG004
		1200mm	FCG005
	15FC x 15FC	300mm	FCG010
		450mm	FCG011
		600mm	FCG012
		900mm	FCG013
		1200mm	FCG014
20mm	20FC x 20MI	600mm	FCG006
		900mm	FCG007
		1000mm	FCG008
		1200mm	FCG009
	20FC x 20FC	600mm	FCG015
		900mm	FCG016
		1000mm	FCG017
		1200mm	FCG018

Features and Benefits

- Available in 10mm and 20mm sizes
- Lengths from 300 – 1200mm
- BSPT Male Threads
- Female cone connection ends (FC)
- 10 year warranty
- AGA approved (AGA7854)
- Natural Gas and LPG
- Contact RWC if you have any size requirements not covered by the specification

Warranty

Reliance Worldwide Corporation (Aust.) Pty. Ltd. (RWC) will either replace or repair any defective goods where the defect arose as a result of manufacture within the warranty period. You may contact RWC at the phone number, address or e-mail shown below for further information or to make a claim.

Visit www.rmc.com.au/warranty to view the warranty statement in full and for further important information.

Standards and Approvals

AS/NZS 1869-2012
AS 4627-2018
Class D or B
AGA Cert Number 7854

Gas Flexible Hose Connectors


Materials

1	Core	Brass: HPB57-3
2	Hex Nut	Brass: HPB57-3
3	Crimp Sleeve	SS304 Stainless Steel
4	Braided Hose	SS304 Stainless Steel
5	Inner Tube	PVC


Technical Specifications

DN10 Class D	
Temperature range	-20°C to 125°C
Maximum inlet pressure	2.5MPa
DN20 Class B	
Temperature range	-20°C to 125°C
Maximum inlet pressure	14kPa

10mm Gas Hose




20mm Gas Hose




Gas Flexible Hose Connectors

Correct Installation



Incorrect Installation



NOTE: Do not twist or stretch connector

NOTE: Avoid excessive bending

